



Flexible and versatile small recessed design

65-degree unidirectional tilt adjustment



Pressure modular assembly



30-degree offset shaft
design

Small cutout, high power
output



High ceiling specific



Video

FIXED

WALL W




FLEXI

RECESSED DOWNLIGHT

/ASHER

ADJUSTABLE






Secondary Optics Supported Processes
Electroplating, Brushing, Spray Coating,
Anodizing



Fixed

FLEXI



WALL WASHER RECESSED DOWNLIGHT



26D tilt design
Four optical design (lens, stretch lens,
optical film, anti-glare cover)



Shared Mounting Components






Quickinfo

2700K, 3000K, 4000K
CRI90, 3 SDCM
L85/50000h
non DIM, 0-10V DIM, DALI-2

Types



Colours



White Black

Light distributions



WW

FLEXI

WALL WASHER RECESSED DOWNLIGHT

Order options

COLOUR TEMPERATURE

2700K

3000K

4000K

FINISH COLOUR

matte white

matte black

BEAM ANGLE FLEXI 55

ww Tilted 20° Beam 48°

BEAM ANGLE FLEXI 75

ww Tilted 20° Beam 72°

BEAM ANGLE FLEXI 100

ww Tilted 22° Beam 52°

FLEXI 55



CRI
>90

COB




IP20

DALI

≤19
UGR

55



WALL WASHER DOWNLIGHT

SYSTEM POWER	COLOUR TEMP	LUMINOUS FLUX	ORDER CODE
9W 36V 200MA	3000K	400lm	51.05522
	4000K	420lm	

FLEXI 75



CRI
>90

COB




IP20

DALI

≤19
UGR

75



WALL WASHER DOWNLIGHT

SYSTEM POWER	COLOUR TEMP	LUMINOUS FLUX	ORDER CODE
15W 36V 350MA	3000K	1123lm	51.07526
	4000K	1179lm	

FLEXI 100



CRI
>90

COB




IP20

DALI

≤19
UGR

100



WALL WASHER DOWNLIGHT

SYSTEM POWER	COLOUR TEMP	LUMINOUS FLUX	ORDER CODE
28W 36V 700MA	3000K	1754lm	51.10013
	4000K	1842lm	




Secondary Optics Supported Processes
Electroplating, Brushing, Spray Coating,
Anodizing



Vertical 30°, Horizontal 350°
With Fall Protection Wire

FLEXI


ADJUSTABLE RECESSED DOWNLIGHT



Light Leak Prevention Design
Cut-off Angle 42°
Optical eccentric design, boosting
efficiency by 10%



Shared Mounting Components
Supports Lenses and Reflector



Quickinfo

2700K, 3000K, 4000K
CRI90, 3 SDCM
L85/50000h
non DIM, 0-10V DIM, DALI-2

Types



Colours



White Black

Light distributions



spot med. flood wide
flood

FLEXI

ADJUSTABLE RECESSED DOWNLIGHT

Order options

COLOUR TEMPERATURE

2700K

3000K

4000K

FINISH COLOUR

matte white

matte black

BEAM ANGLE FLEXI 55

spot 15°

medium 23°

flood 35°

wide flood 51°

BEAM ANGLE FLEXI 75

spot 19°

medium 29°

flood 40°

wide flood 50°

BEAM ANGLE FLEXI 100

spot 25°

medium 32°

flood 44°

wide flood 52°

FLEXI 55



CRI
>90

COB




350°
30°

IP20

DALI

≤19
UGR

55



ADJUSTABLE DOWNLIGHT

SYSTEM POWER	COLOUR TEMP	LUMINOUS FLUX	ORDER CODE
10W 36V 250MA	3000K	620lm	52.05535
	4000K	651lm	

FLEXI 75



CRI
>90

COB




350°
30°

IP20

DALI

≤19
UGR

75



ADJUSTABLE DOWNLIGHT

SYSTEM POWER	COLOUR TEMP	LUMINOUS FLUX	ORDER CODE
15W 36V 350MA	3000K	1528lm	52.07529
	4000K	1604lm	

FLEXI 100



CRI
>90

COB




350°
30°

IP20

DALI

≤19
UGR

100



ADJUSTABLE DOWNLIGHT

SYSTEM POWER	COLOUR TEMP	LUMINOUS FLUX	ORDER CODE
28W 36V 700MA	3000K	3021lm	52.10029
	4000K	3172lm	




Secondary Optics Supported Processes
Electroplating, Brushing, Spray Coating,
Anodizing



Fixed

FLEXI

RECESSED DOWNLIGHT



Light Leak Prevention Design
Cut-off Angle 42°
Optical eccentric design, boosting
efficiency by 10%



Shared Mounting Components
Supports Lenses and Reflector



Quickinfo

2700K, 3000K, 4000K
CRI90, 3 SDCM
L85/50000h
non DIM, 0-10V DIM, DALI-2

Types



Colours



White Black

Light distributions



spot med. flood wide
flood

FLEXI

RECESSED DOWNLIGHT

Order options

COLOUR TEMPERATURE

2700K

3000K

4000K

FINISH COLOUR

matte white

matte black

BEAM ANGLE FLEXI 55

spot 15°

medium 22°

flood 37°

wide flood 49°

BEAM ANGLE FLEXI 75

spot 19°

medium 29°

flood 40°

wide flood 50°

BEAM ANGLE FLEXI 100

spot 25°

medium 31°

flood 42°

wide flood 49°

FLEXI 55



CRI
>90

COB




IP20

DALI

≤19
UGR

55



RECESSED DOWNLIGHT

SYSTEM POWER	COLOUR TEMP	LUMINOUS FLUX	ORDER CODE
9W 36V 250MA	3000K	625lm	51.05521
	4000K	656lm	

FLEXI 75



CRI
>90

COB




IP20

DALI

≤19
UGR

75



RECESSED DOWNLIGHT

SYSTEM POWER	COLOUR TEMP	LUMINOUS FLUX	ORDER CODE
15W 36V 350MA	3000K	1547lm	51.07525
	4000K	1624lm	

FLEXI 100



CRI
>90

COB




IP20

DALI

≤19
UGR

100



RECESSED DOWNLIGHT


SYSTEM POWER	COLOUR TEMP	LUMINOUS FLUX	ORDER CODE
28W 36V 700MA	3000K	3081lm	51.10012
	4000K	3235lm	



30-degree adjustable



Low glare






e, fixed

Fixed





Heat sink is a module,
interchangeable




Structural supports
ens and reflector



Mounting module,
interchangeable

OPTIMAX

RECESSED DOWNLIGHT






Quickinfo

2700K, 3000K, 4000K
CRI90, 3 SDCM
L85/50000h
non DIM, 0-10V DIM, DALI-2

Types



Colours



White Black

Light distributions



spot med. flood wide
flood

OPTIMAX

RECESSED DOWNLIGHT

Order options

COLOUR TEMPERATURE

2700K

3000K

4000K

FINISH COLOUR

sandy white

sandy black

BEAM ANGLE ROUND 50

spot 17°

medium 25°

flood 38°

wide flood 47°

BEAM ANGLE FIXED 50

spot 19°

medium 28°

flood 40°

wide flood 52°

BEAM ANGLE ADJUSTABLE 50

spot 19°


medium 28°

flood 41°

wide flood 51°



50



50

OPTIMAX 50 Round



CRI
>90

COB



IP20

DALI


≤6
UGR

RECESSED DOWNLIGHT

SYSTEM POWER	COLOUR TEMP	LUMINOUS FLUX	ORDER CODE
8W 36V 180MA	3000K	514lm	51.05012
	4000K	539lm	



50



50

OPTIMAX 50 Fixed



CRI
>90

COB



IP20

DALI


≤10
UGR

RECESSED DOWNLIGHT

SYSTEM POWER	COLOUR TEMP	LUMINOUS FLUX	ORDER CODE
8W 36V 180MA	3000K	589lm	51.05011
	4000K	618lm	



50



50

OPTIMAX 50 Adjustable



CRI
>90

COB



IP20

DALI

≤12
UGR

ADJUSTABLE DOWNLIGHT


SYSTEM POWER	COLOUR TEMP	LUMINOUS FLUX	ORDER CODE
8W 36V 180MA	3000K	601lm	52.05015
	4000K	631lm	



Quickinfo

2700K, 3000K, 4000K
CRI90, 3 SDCM
L85/50000h
non DIM, 0-10V DIM, DALI-2

Types



Colours



White Black

Light distributions



spot med. flood wide
flood

OPTIMAX

RECESSED DOWNLIGHT

Order options

COLOUR TEMPERATURE

2700K

3000K

4000K

FINISH COLOUR

sandy white

sandy black

BEAM ANGLE ROUND 65

spot 18°

medium 27°

flood 39°

wide flood 45°

BEAM ANGLE FIXED 65

spot 21°

medium 31°

flood 42°

wide flood 51°

BEAM ANGLE ADJUSTABLE 65

spot 20°

medium 30°

flood 42°

wide flood 51°



OPTIMAX 65 Round



RECESSED DOWNLIGHT

SYSTEM POWER	COLOUR TEMP	LUMINOUS FLUX	ORDER CODE
14W 36V 350MA	3000K	963lm	51.06513
	4000K	1011lm	



OPTIMAX 65 Fixed




RECESSED DOWNLIGHT

SYSTEM POWER	COLOUR TEMP	LUMINOUS FLUX	ORDER CODE
14W 36V 350MA	3000K	1147lm	51.06512
	4000K	1204lm	




OPTIMAX 65 Adjustable




ADJUSTABLE DOWNLIGHT

SYSTEM POWER	COLOUR TEMP	LUMINOUS FLUX	ORDER CODE
14W 36V 350MA	3000K	1175lm	52.06513
	4000K	1233lm	

**MAGFIT**

RECESSED DOWNLIGHT





Quickinfo

2700K, 3000K, 4000K
CRI90, 3 SDCM
L85/50000h
non DIM, 0-10V DIM, DALI-2

Types



Colours



White Black

Light distributions



spot med. flood wide
flood

MAGFIT

RECESSED DOWNLIGHT

Order options

COLOUR TEMPERATURE

2700K

3000K

4000K

FINISH COLOUR

matte white

matte black

BEAM ANGLE MAGFIT 45

spot 20°

medium 24°

flood 36°

wide flood 58°

BEAM ANGLE MAGFIT 55

spot 21°

medium 26°

flood 41°

wide flood 56°

BEAM ANGLE MAGFIT 65


spot 21°

medium 31°

flood 42°

wide flood 52°

MAGFIT 45



45



CRI
>90

COB



350°
30°

IP20

DALI

≤15
UGR

ADJUSTABLE DOWNLIGHT

SYSTEM POWER	COLOUR TEMP	LUMINOUS FLUX	ORDER CODE
6W 36V 150MA	3000K	503lm	52.04527
	4000K	528lm	

MAGFIT 55



55



CRI
>90

COB



350°
30°

IP20

DALI

≤15
UGR

ADJUSTABLE DOWNLIGHT

SYSTEM POWER	COLOUR TEMP	LUMINOUS FLUX	ORDER CODE
10W 36V 250MA	3000K	942lm	52.05536
	4000K	989lm	

MAGFIT 65



65



CRI
>90

COB



350°
30°


IP20

DALI

≤15
UGR

ADJUSTABLE DOWNLIGHT


SYSTEM POWER	COLOUR TEMP	LUMINOUS FLUX	ORDER CODE
14W 36V 350MA	3000K	1595lm	52.06517
	4000K	1674lm	



Quickinfo

2700K, 3000K, 4000K
CRI90, 3 SDCM
L85/50000h
non DIM, 0-10V DIM, DALI-2

Types



Colours



White Black

Light distributions



spot med. flood wide
flood

VOLI

RECESSED DOWNLIGHT


Order options

COLOUR TEMPERATURE
2700K
3000K
4000K

FINISH COLOUR
sandy white
sandy black

BEAM ANGLE VOLI 75
spot 19°
medium 29°
flood 40°
wide flood 50°

BEAM ANGLE VOLI 95
spot 25°
medium 31°
flood 42°
wide flood 49°



VOLI 75

CRI >90

COB

350°
23°


IP20

DALI

≤19
UGR

ADJUSTABLE DOWNLIGHT

SYSTEM POWER	COLOUR TEMP	LUMINOUS FLUX	ORDER CODE
14W 36V 350MA	3000K	1123lm	52.07531
	4000K	1179lm	



VOLI 95

CRI >90

COB

350°
23°

IP20

DALI

≤19
UGR

ADJUSTABLE DOWNLIGHT

SYSTEM POWER	COLOUR TEMP	LUMINOUS FLUX	ORDER CODE
25W 36V 600MA	3000K	2900lm	52.09535
	4000K	3045lm	

65mm Cut Out
12W
511LM

85mm Cut Out
20W
1360LM




WALLI

WALL WASHER RECESSED DOWNLIGHT


105mm Cut Out
30W
1707LM

105mm Cut Out
30W
1707LM



**WALLI**

WALL WASHER RECESSED DOWNLIGHT





Quickinfo

2700K, 3000K, 4000K
CRI90, 3 SDCM
L85/50000h
non DIM, 0-10V DIM, DALI-2

Types



Colours



White Black

Light distributions



WW

WALLI

WALL WASHER RECESSED DOWNLIGHT

Order options

COLOUR TEMPERATURE

2700K

3000K

4000K

FINISH COLOUR

sandy white

sandy black

BEAM ANGLE WALLI 65

ww Tilted 18° Beam 48°

BEAM ANGLE WALLI 85


ww Tilted 25° Beam 51°

BEAM ANGLE WALLI 105

ww Tilted 20° Beam 40°



65



WALLI 65



CRI
>90

COB



350°
15°

IP20

DALI


≤19
UGR

WALL WASHER DOWNLIGHT

SYSTEM POWER	COLOUR TEMP	LUMINOUS FLUX	ORDER CODE
12W 36V 300MA	3000K	511lm	52.06516
	4000K	536lm	



85



WALLI 85



CRI
>90

COB



350°
15°

IP20

DALI


≤19
UGR

WALL WASHER DOWNLIGHT

SYSTEM POWER	COLOUR TEMP	LUMINOUS FLUX	ORDER CODE
20W 36V 500MA	3000K	1366lm	52.08525
	4000K	1434lm	



105



WALLI 105



CRI
>90

COB



350°
15°

IP20

DALI

≤19
UGR

WALL WASHER DOWNLIGHT

SYSTEM POWER	COLOUR TEMP	LUMINOUS FLUX	ORDER CODE
30W 36V 700MA	3000K	1707lm	52.10512
	4000K	1792lm	



55mm Cut Out
14W
1542LM





75mm Cut Out
32W
3832LM






INTERO



RECESSED DOWNLIGHT



Cut Out
2W
5LM

95mm Cut Out
42W
4992LM





Quickinfo

2700K, 3000K, 4000K
CRI90, 3 SDCM
L85/50000h
non DIM, 0-10V DIM, DALI-2

Types



Colours



White Black

Light distributions



spot med. flood wide
flood

INTERO

RECESSED DOWNLIGHT

Order options

COLOUR TEMPERATURE

2700K

3000K

4000K

FINISH COLOUR

sandy white

sandy black

BEAM ANGLE INTERO 55

spot 29°

medium 35°

flood 47°

wide flood 58°

BEAM ANGLE INTERO 75

spot 32°

medium 40°

flood 48°

wide flood 58°

BEAM ANGLE INTERO 95


spot 26°

medium 31°


flood 41°

wide flood 49°

INTERO 55



55



CRI
>90

COB



350°
20°

IP20

DALI

≤13
UGR


ADJUSTABLE DOWNLIGHT

SYSTEM POWER	COLOUR TEMP	LUMINOUS FLUX	ORDER CODE
14W 36V 350MA	3000K	1469lm	52.05523
	4000K	1542lm	

INTERO 75



75



CRI
>90

COB



350°
20°

IP20

DALI

≤20
UGR


ADJUSTABLE DOWNLIGHT

SYSTEM POWER	COLOUR TEMP	LUMINOUS FLUX	ORDER CODE
32W 36V 800MA	3000K	3653lm	52.07523
	4000K	3835lm	

INTERO 95



95



CRI
>90

COB



350°
20°


IP20

DALI

≤17
UGR

ADJUSTABLE DOWNLIGHT

SYSTEM POWER	COLOUR TEMP	LUMINOUS FLUX	ORDER CODE
42W 36V 1050MA	3000K	4755lm	52.09531
	4000K	4992lm	



SLIM

RECESSED DOWNLIGHT

Quickinfo


2700K, 3000K, 4000K

CRI90, 3 SDCM

L85/50000h

non DIM, 0-10V DIM, DALI-2

Types



Colours



White Black

Light distributions



spot med. flood wide
flood

Order options

COLOUR TEMPERATURE

2700K

3000K

4000K

FINISH COLOUR

sandy white

sandy black

BEAM ANGLE SLIM 55

spot 25°

medium 32°

flood 42°

wide flood 46°

BEAM ANGLE SLIM 75

spot 30°

medium 40°

flood 46°

wide flood 52°

BEAM ANGLE SLIM 75

spot 31°

medium 40°

flood 46°

wide flood 51°

BEAM ANGLE SLIM 95

spot 27°

medium 32°

flood 41°

wide flood 51°

SLIM 55



55



CRI
>90


COB



IP20

DALI

≤18
UGR



RECESSED DOWNLIGHT

SYSTEM POWER	COLOUR TEMP	LUMINOUS FLUX	ORDER CODE
14W 36V 350MA	3000K	1493lm	51.05516
	4000K	1567lm	

SLIM 75



75



CRI
>90


COB



IP20

DALI


≤17
UGR



RECESSED DOWNLIGHT

SYSTEM POWER	COLOUR TEMP	LUMINOUS FLUX	ORDER CODE
24W 36V 600MA	3000K	2958lm	51.07518
	4000K	3105lm	

SLIM 75



75



CRI
>90


COB



IP20

DALI

≤17
UGR



RECESSED DOWNLIGHT

SYSTEM POWER	COLOUR TEMP	LUMINOUS FLUX	ORDER CODE
32W 36V 800MA	3000K	3530lm	51.07519
	4000K	3706lm	

SLIM 95



95



CRI
>90


COB



IP20






DALI

≤17
UGR






RECESSED DOWNLIGHT

SYSTEM POWER	COLOUR TEMP	LUMINOUS FLUX	ORDER CODE
40W 36V 1050MA	3000K	4374lm	51.09511
	4000K	4592lm	





X-DRIVE

RECESSED DOWNLIGHT




Purple Copper Heat Conduction
55/ 65/ 75mm Cut out
Maximum 36W
Max Lumen 4200lm
Horizontal and vertical adjustable



Quickinfo

2700K, 3000K, 4000K
CRI90, 3 SDCM
L85/50000h
non DIM, 0-10V DIM, DALI-2

Types



Colours



White Black

Light distributions



spot med. flood wide
flood

X-DRIVE

RECESSED DOWNLIGHT

Order options

COLOUR TEMPERATURE

2700K

3000K

4000K

FINISH COLOUR

sandy white

sandy black

BEAM ANGLE X-DRIVE 55

spot 30°

medium 35°

flood 49°

wide flood 59°

BEAM ANGLE X-DRIVE 65

spot 31°

medium 40°

flood 49°

wide flood 59°

BEAM ANGLE X-DRIVE 75

spot 29°

medium 35°

flood 49°

wide flood 57°

X-DRIVE 55



CRI
>90

COB




IP20

DALI

≤18
UGR


55



ADJUSTABLE DOWNLIGHT

SYSTEM POWER	COLOUR TEMP	LUMINOUS FLUX	ORDER CODE
18W 36V 400MA	3000K	1733lm	52.05533
	4000K	1819lm	

X-DRIVE 65



CRI
>90

COB




IP20

DALI

≤18
UGR

65



ADJUSTABLE DOWNLIGHT

SYSTEM POWER	COLOUR TEMP	LUMINOUS FLUX	ORDER CODE
28W 36V 700MA	3000K	3127lm	52.06515
	4000K	3283lm	

X-DRIVE 75



CRI
>90

COB




IP20

DALI

≤18
UGR

75



ADJUSTABLE DOWNLIGHT

SYSTEM POWER	COLOUR TEMP	LUMINOUS FLUX	ORDER CODE
35W 36V 900MA	3000K	4126lm	52.07530
	4000K	4332lm	

Recessed lighting fixtures for high-ceiling use, with a maximum output of 9500 lumens.



Video



40W



60W

HICORE

RECESSED DOWNLIGHT



80W



Metal Base reflector
Aluminum Anodized Optical



Three mounting clips support 8-25mm
ceiling

Dust cover



Dust cover design protects light source
Secondary optics secured by mechanical
structure

anti-drop safety hook



Fixture anti-drop safety hook
1070 heat sink with ultra-fast thermal
conductivity



Quickinfo

2700K, 3000K, 4000K
CRI90, 3 SDCM
L85/50000h
non DIM, 0-10V DIM, DALI-2

Types



Colours



White Black

Light distributions



spot med. flood wide
flood

HICORE

RECESSED DOWNLIGHT

Order options

COLOUR TEMPERATURE

2700K

3000K

4000K

FINISH COLOUR

sandy white

sandy black

BEAM ANGLE HICORE 110

spot 22°

medium --°

flood 42°

wide flood 60°

BEAM ANGLE HICORE 135

spot 21°

medium 38°

flood 56°

wide flood 66°

BEAM ANGLE HICORE 160

spot 26°

medium 36°


flood 46°

wide flood 70°

HICORE 110



110



CRI
>90

COB



IP20

DALI

≤17
UGR


RECESSED DOWNLIGHT

SYSTEM POWER	COLOUR TEMP	LUMINOUS FLUX	ORDER CODE
40W 36V 1050MA	3000K	4769lm	51.11011
	4000K	5007lm	

HICORE 135



135



CRI
>90

COB



IP20

DALI

≤19
UGR


RECESSED DOWNLIGHT

SYSTEM POWER	COLOUR TEMP	LUMINOUS FLUX	ORDER CODE
60W 36V 1500MA	3000K	7546lm	51.13511
	4000K	7923lm	

HICORE 160



160



CRI
>90

COB





IP20

DALI




≤22
UGR

RECESSED DOWNLIGHT

SYSTEM POWER	COLOUR TEMP	LUMINOUS FLUX	ORDER CODE
80W 36V 2100MA	3000K	9122lm	51.16011
	4000K	9578lm	

**VERO**

RECESSED DOWNLIGHT





Quickinfo

2700K, 3000K, 4000K
CRI90, 3 SDCM
L85/50000h
non DIM, 0-10V DIM, DALI-2

Types



Colours



White Black

Light distributions



spot flood

VERO

RECESSED DOWNLIGHT

Order options

COLOUR TEMPERATURE

2700K

3000K

4000K

FINISH COLOUR

matte white

matte black

BEAM ANGLE VERO 108

spot 27°

flood 44°

BEAM ANGLE VERO 70

spot 27°

flood 44°

BEAM ANGLE VERO 108

spot 27°

flood 44°

BEAM ANGLE VERO 70

spot 27°

flood 44°

VERO 108



CRI
>90


COB



IP20

DALI


≤10
UGR



ADJUSTABLE DOWNLIGHT

SYSTEM POWER	COLOUR TEMP	LUMINOUS FLUX	ORDER CODE
8W 36V 180MA	3000K	446lm	52.10811
	4000K	469lm	

VERO 70



CRI
>90


COB



IP20

DALI

≤10
UGR



RECESSED DOWNLIGHT

SYSTEM POWER	COLOUR TEMP	LUMINOUS FLUX	ORDER CODE
8W 36V 180MA	3000K	446lm	52.07012
	4000K	469lm	

VERO 108



CRI
>90


COB



IP20

DALI

≤10
UGR



ADJUSTABLE DOWNLIGHT

SYSTEM POWER	COLOUR TEMP	LUMINOUS FLUX	ORDER CODE
8W 36V 180MA	3000K	446lm	57.10811
	4000K	469lm	

VERO 70



CRI
>90


COB



IP20

DALI

≤10
UGR



RECESSED DOWNLIGHT

SYSTEM POWER	COLOUR TEMP	LUMINOUS FLUX	ORDER CODE
8W 36V 180MA	3000K	446lm	57.07013
	4000K	469lm	

**ORBI**

RECESSED DOWNLIGHT





Quickinfo

2700K, 3000K, 4000K
CRI90, 3 SDCM
L85/50000h
non DIM, 0-10V DIM, DALI-2

Types



Colours



White Black

Light distributions



spot med. flood wide
flood

ORBI

RECESSED DOWNLIGHT

Order options

COLOUR TEMPERATURE

2700K

3000K

4000K

FINISH COLOUR

sandy white

sandy black

BEAM ANGLE ORBI 35 L0

spot 28°

medium 35°

flood 38°

wide flood 53°

BEAM ANGLE ORBI 35 L2

spot 28°

medium 35°

flood 38°

wide flood 53°

BEAM ANGLE ORBI 35 L4

spot 28°

medium 35°

flood 38°

wide flood 53°

ORBI 35 L0



35



CRI
>90

COB



350°
45°

IP20

DALI

≤19
UGR

ADJUSTABLE DOWNLIGHT

SYSTEM POWER	COLOUR TEMP	LUMINOUS FLUX	ORDER CODE
4W 12V 250MA	3000K	301lm	55.03525
	4000K	316lm	

ORBI 35 L2



75x35



CRI
>90

COB



350°
45°

IP20

DALI

≤19
UGR

ADJUSTABLE DOWNLIGHT

SYSTEM POWER	COLOUR TEMP	LUMINOUS FLUX	ORDER CODE
4WX2 12V 250MA	3000K	2X301lm	55.03526
	4000K	2X316lm	

ORBI 35 L4



155x35



CRI
>90

COB



350°
45°


IP20


DALI

≤19
UGR


ADJUSTABLE DOWNLIGHT

SYSTEM POWER	COLOUR TEMP	LUMINOUS FLUX	ORDER CODE
4WX4 12V 250MA	3000K	4X301lm	55.03527
	4000K	4X316lm	












SHOWLITE
CABINET LIGHT






Quickinfo

2700K, 3000K, 4000K
CRI90, 3 SDCM
L85/50000h
non DIM, 0-10V DIM, DALI-2

Types



Colours



White Black

Light distributions



spot med. flood wide flood
flood

SHOWLITE

CABINET LIGHT

Order options

COLOUR TEMPERATURE

2700K

3000K

4000K

FINISH COLOUR

matte white

matte black

BEAM ANGLE SHOWLITE 50

spot 28°

medium 35°

flood 38°

wide flood 53°

BEAM ANGLE SHOWLITE 45

spot 19°

medium 23°

flood 28°

wide flood 46°

BEAM ANGLE SHOWLITE 45

spot 20°

medium 23°

flood 28°

wide flood 40°

SHOWLITE 50



50



CRI
>90

COB



350°
65°

IP20

DALI

≤19
UGR

CABINET LIGHT

SYSTEM POWER

COLOUR TEMP

LUMINOUS FLUX

ORDER CODE

4W 12V 250MA

3000K

301lm

52.05013

4000K

316lm

SHOWLITE 45



45



CRI
>90

COB



350°
18°

IP20

DALI

≤14
UGR

CABINET LIGHT

SYSTEM POWER

COLOUR TEMP

LUMINOUS FLUX

ORDER CODE

4W 12V 250MA

3000K

285lm

52.04526

4000K

299lm

SHOWLITE 45



45



CRI
>90

COB



350°
18°

IP20

DALI

≤15
UGR

CABINET LIGHT

SYSTEM POWER

COLOUR TEMP

LUMINOUS FLUX

ORDER CODE

4W 12V 250MA


3000K

277lm

52.04525

4000K


290lm



Quickinfo

2700K, 3000K, 4000K
CRI90, 3 SDCM
L85/50000h
non DIM, 0-10V DIM, DALI-2

Types



Colours



White Black

Light distributions



WW

SHOWLITE

CABINET LIGHT

Order options

COLOUR TEMPERATURE

2700K

3000K

4000K

FINISH COLOUR

matte white

matte black

BEAM ANGLE SHOWLITE 30

ww Tilted 10° Beam 45°

BEAM ANGLE SHOWLITE 50

ww Tilted 10° Beam 48°

SHOWLITE 30



CRI
>90

COB




IP20

DALI

≤17
UGR

30



CABINET LIGHT

SYSTEM POWER

COLOUR TEMP

LUMINOUS FLUX

ORDER CODE

4W 12V 250MA

3000K


150lm

51.03027

4000K

158lm

SHOWLITE 50



CRI
>90

COB




IP20

DALI

≤26
UGR

50



CABINET LIGHT

SYSTEM POWER

COLOUR TEMP

LUMINOUS FLUX

ORDER CODE

9W 36V 200MA

3000K

425lm

51.05013


4000K

446lm



Video

Modular, press-to-open



MINI PRO

RECESSED DOWNLIGHT




Fully modular with push-to-release design




Horizontal and vertical
adjustment across all models



Trim installation with glare
reflector



Trimless installation with ultimate
glare



Quickinfo

2700K, 3000K, 4000K
CRI90, 3 SDCM
L85/50000h
non DIM, 0-10V DIM, DALI-2

Types



Colours



White Black

Light distributions



spot med. flood wide
flood

MINI PRO

RECESSED DOWNLIGHT

Order options

COLOUR TEMPERATURE

2700K

3000K

4000K

FINISH COLOUR

matte white

matte black

BEAM ANGLE MINI PRO 55

spot 17°

medium 23°

flood 34°

wide flood 55°

BEAM ANGLE MINI PRO 55

spot 17°

medium 23°

flood 34°

wide flood 55°

BEAM ANGLE MINI PRO 65

spot 17°

medium 23°

flood 34°

wide flood 55°

BEAM ANGLE MINI PRO 55

spot 18°


medium 23°

flood 35°

wide flood 50°



55



MINI PRO 55



ADJUSTABLE DOWNLIGHT

SYSTEM POWER	COLOUR TEMP	LUMINOUS FLUX	ORDER CODE
8W 36V 180MA	3000K	684lm	52.05527
	4000K	718lm	



55



MINI PRO 55




ADJUSTABLE DOWNLIGHT

SYSTEM POWER	COLOUR TEMP	LUMINOUS FLUX	ORDER CODE
8W 36V 180MA	3000K	627lm	52.05526
	4000K	659lm	



65




MINI PRO 65




ADJUSTABLE DOWNLIGHT

SYSTEM POWER	COLOUR TEMP	LUMINOUS FLUX	ORDER CODE
8W 36V 180MA	3000K	627lm	57.06511
	4000K	659lm	



55



MINI PRO 55




ADJUSTABLE DOWNLIGHT

SYSTEM POWER	COLOUR TEMP	LUMINOUS FLUX	ORDER CODE
8W 36V 180MA	3000K	547lm	57.05516
	4000K	574lm	

Full range of ball-bearing



structure, removable and share
modules



Trim installation



Quickinfo

2700K, 3000K, 4000K
CRI90, 3 SDCM
L85/50000h
non DIM, 0-10V DIM, DALI-2

Types



Colours



White Black

Light distributions



spot med. flood wide
flood

MINI PRO

RECESSED DOWNLIGHT

Order options

COLOUR TEMPERATURE

2700K

3000K

4000K

FINISH COLOUR

matte white

matte black

BEAM ANGLE MINI PRO 45

spot 18°

medium 23°

flood 32°

wide flood 45°

BEAM ANGLE MINI PRO 45

spot 18°

medium 23°

flood 32°

wide flood 45°

BEAM ANGLE MINI PRO 45

spot 18°

medium 23°


flood 32°

wide flood 45°

MINI PRO 45



45



CRI
>90

COB



IP20

DALI

≤18
UGR


RECESSED DOWNLIGHT

SYSTEM POWER	COLOUR TEMP	LUMINOUS FLUX	ORDER CODE
8W 36V 180MA	3000K	608lm	51.04523
	4000K	638lm	

MINI PRO 45



45



CRI
>90

COB



IP20

DALI

≤18
UGR


RECESSED DOWNLIGHT

SYSTEM POWER	COLOUR TEMP	LUMINOUS FLUX	ORDER CODE
8W 36V 180MA	3000K	608lm	60.04513
	4000K	638lm	

MINI PRO 45



43



CRI
>90

COB



IP20

DALI


≤18
UGR

RECESSED DOWNLIGHT

SYSTEM POWER	COLOUR TEMP	LUMINOUS FLUX	ORDER CODE
8W 36V 180MA	3000K	608lm	60.04515
	4000K	638lm	

Narrow-trim recessed lights, with
custom spring clips designed for
different ceiling types.





Quickinfo

2700K, 3000K, 4000K
CRI90, 3 SDCM
L85/50000h
non DIM, 0-10V DIM, DALI-2

Types



Colours



White Black

Light distributions



spot med. flood wide
flood

MINI PRO

RECESSED DOWNLIGHT


Order options

COLOUR TEMPERATURE
2700K
3000K
4000K

FINISH COLOUR
matte white
matte black

BEAM ANGLE MINI PRO 38
spot 18°
medium 23°
flood 32°
wide flood 45°

BEAM ANGLE MINI PRO 38
spot 18°
medium 23°
flood 32°
wide flood 45°



MINI PRO 38

CRI >90


COB

IP20

DALI

≤18 UGR

38



RECESSED DOWNLIGHT

SYSTEM POWER	COLOUR TEMP	LUMINOUS FLUX	ORDER CODE
8W 36V 180MA	3000K	608lm	51.03825
	4000K	638lm	



MINI PRO 38

CRI >90


COB

IP20

DALI

≤18 UGR

38



RECESSED DOWNLIGHT

SYSTEM POWER	COLOUR TEMP	LUMINOUS FLUX	ORDER CODE
8W 36V 180MA	3000K	608lm	51.03823
	4000K	638lm	

**MINI**

RECESSED DOWNLIGHT





Quickinfo


2700K, 3000K, 4000K

CRI90, 3 SDCM

L85/50000h

non DIM, 0-10V DIM, DALI-2

Types



Colours



White Black

Light distributions



spot med. flood wide
flood

MINI

RECESSED DOWNLIGHT

Order options

COLOUR TEMPERATURE

2700K

3000K

4000K

FINISH COLOUR

matte white

matte black

BEAM ANGLE MINI 30

spot 21°

medium 27°

flood 39°

wide flood 57°

BEAM ANGLE MINI 45

spot 19°

medium 22°

flood 31°

wide flood 46°

BEAM ANGLE MINI 45


spot 19°

medium 22°


flood 31°

wide flood 46°

MINI 30



30



CRI
>90

COB



IP20


DALI

≤18
UGR


RECESSED DOWNLIGHT

SYSTEM POWER	COLOUR TEMP	LUMINOUS FLUX	ORDER CODE
6W 36V 150MA	3000K	353lm	51.03015
	4000K	370lm	

MINI 45



45



CRI
>90

COB



IP20

DALI

≤18
UGR


RECESSED DOWNLIGHT

SYSTEM POWER	COLOUR TEMP	LUMINOUS FLUX	ORDER CODE
6W 36V 150MA	3000K	368lm	51.04511
	4000K	386lm	

MINI 45



45



CRI
>90

COB



IP20

DALI

≤18
UGR

ADJUSTABLE DOWNLIGHT

SYSTEM POWER	COLOUR TEMP	LUMINOUS FLUX	ORDER CODE
6W 36V 150MA	3000K	368lm	52.04512
	4000K	386lm	



Quickinfo

2700K, 3000K, 4000K
CRI90, 3 SDCM
L85/50000h
non DIM, 0-10V DIM, DALI-2

Types



Colours



White Black

Light distributions



spot med. flood wide
flood

MINI

RECESSED DOWNLIGHT

Order options

COLOUR TEMPERATURE

2700K

3000K

4000K

FINISH COLOUR

matte white

matte black

BEAM ANGLE MINI 40

spot 18°

medium 22°

flood 34°

wide flood 46°

BEAM ANGLE MINI 40


spot 18°

medium 22°

flood 34°

wide flood 46°

MINI 40



CRI
>90

COB




IP20

DALI

≤16
UGR


40



RECESSED DOWNLIGHT

SYSTEM POWER	COLOUR TEMP	LUMINOUS FLUX	ORDER CODE
8W 36V 180MA	3000K	471lm	51.04011
	4000K	494lm	

MINI 40



CRI
>90

COB




IP20

DALI



≤16
UGR

40




ADJUSTABLE DOWNLIGHT

SYSTEM POWER	COLOUR TEMP	LUMINOUS FLUX	ORDER CODE
8W 36V 180MA	3000K	471lm	52.04018
	4000K	494lm	

**NOVAL**

RECESSED DOWNLIGHT






Quickinfo

2700K, 3000K, 4000K
CRI90, 3 SDCM
L85/50000h
non DIM, 0-10V DIM, DALI-2

Types



Colours



White Black

Light distributions



spot med. flood wide
flood

NOVAL

RECESSED DOWNLIGHT

Order options

COLOUR TEMPERATURE

2700K

3000K

4000K

FINISH COLOUR

matte white

matte black

BEAM ANGLE NOVAL 23 L0

spot 17°

medium 26°

flood 31°

wide flood 53°

BEAM ANGLE NOVAL 23 L1

spot 17°

medium 26°

flood 31°

wide flood 53°

BEAM ANGLE NOVAL 23 L2

spot 17°

medium 26°

flood 31°

wide flood 53°

NOVAL 23 L0



CRI

>90


COB



IP20

≤9
UGR

23



SEMI-RECESSED SPOTLIGHT

SYSTEM POWER	COLOUR TEMP	LUMINOUS FLUX	ORDER CODE
4W 36V 80MA	3000K	197lm	56.02311
	4000K	207lm	

NOVAL 23 L1



CRI

>90


COB



IP20

≤9
UGR

23x23



SEMI-RECESSED SPOTLIGHT

SYSTEM POWER	COLOUR TEMP	LUMINOUS FLUX	ORDER CODE
4W 36V 80MA	3000K	197lm	56.02312
	4000K	207lm	

NOVAL 23 L2



CRI

>90


COB



IP20



≤9
UGR

62x23



SEMI-RECESSED SPOTLIGHT


SYSTEM POWER	COLOUR TEMP	LUMINOUS FLUX	ORDER CODE
4WX2 36V 80MA	3000K	2X197lm	56.02313
	4000K	2X207lm	



Quickinfo

2700K, 3000K, 4000K
CRI90, 3 SDCM
L85/50000h
non DIM, 0-10V DIM, DALI-2

Types



Colours



White Black

Light distributions



spot med. flood wide
flood

NOVAL

RECESSED DOWNLIGHT

Order options

COLOUR TEMPERATURE

2700K

3000K

4000K

FINISH COLOUR

matte white

matte black

BEAM ANGLE NOVAL 37 L0

spot 18°

medium 23°

flood 33°

wide flood 42°

BEAM ANGLE NOVAL 37 L1

spot 18°

medium 23°

flood 33°

wide flood 42°

BEAM ANGLE NOVAL 37 L2

spot 18°

medium 23°

flood 33°

wide flood 42°

NOVAL 37 L0



CRI
>90

COB




IP20

DALI

≤9
UGR

37



SEMI-RECESSED SPOTLIGHT

SYSTEM POWER	COLOUR TEMP	LUMINOUS FLUX	ORDER CODE
6W 36V 150MA	3000K	478lm	56.03711
	4000K	502lm	

NOVAL 37 L1



CRI
>90

COB




IP20

DALI

≤9
UGR

37x37



SEMI-RECESSED SPOTLIGHT

SYSTEM POWER	COLOUR TEMP	LUMINOUS FLUX	ORDER CODE
6W 36V 150MA	3000K	478lm	56.03712
	4000K	502lm	

NOVAL 37 L2



CRI
>90

COB




IP20

DALI

≤9
UGR

96x37



SEMI-RECESSED SPOTLIGHT


SYSTEM POWER	COLOUR TEMP	LUMINOUS FLUX	ORDER CODE
6WX2 36V 150MA	3000K	2X478lm	56.03713
	4000K	2X502lm	



Quickinfo

2700K, 3000K, 4000K
 CRI90, 3 SDCM
 L85/50000h
 non DIM, 0-10V DIM, DALI-2

Types



Colours



White Black

Light distributions



spot med. flood wide
 flood

EMMA

SEMI-RECESSED SPOT LIGHT

Order options

COLOUR TEMPERATURE

2700K

3000K

4000K

FINISH COLOUR

sandy white

sandy black

BEAM ANGLE EMMA 45

spot 19°

medium 29°

flood 44°

wide flood 56°

BEAM ANGLE EMMA 62

spot 18°

medium 27°

flood 38°

wide flood 54°

BEAM ANGLE EMMA 73

spot 14°

medium 28°

flood 40°

wide flood 50°

BEAM ANGLE EMMA 90

spot 16°


medium 20°

flood 30°

wide flood 45°



40



EMMA 45



CRI
>90

COB



350°
90°

IP20


DALI

SEMI-RECESSED SPOTLIGHT

SYSTEM POWER	COLOUR TEMP	LUMINOUS FLUX	ORDER CODE
11W 36V 250MA	3000K	935lm	56.04011
	4000K	981lm	



55



EMMA 62



CRI
>90

COB



350°
90°

IP20


DALI

SEMI-RECESSED SPOTLIGHT

SYSTEM POWER	COLOUR TEMP	LUMINOUS FLUX	ORDER CODE
14W 36V 350MA	3000K	1627lm	56.05518
	4000K	1708lm	



65



EMMA 73



CRI
>90

COB



350°
90°

IP20


DALI

SEMI-RECESSED SPOTLIGHT

SYSTEM POWER	COLOUR TEMP	LUMINOUS FLUX	ORDER CODE
24W 36V 600MA	3000K	2963lm	56.06511
	4000K	3111lm	



80



EMMA 90



CRI
>90

COB




350°
90°

IP20


DALI

SEMI-RECESSED SPOTLIGHT




SYSTEM POWER	COLOUR TEMP	LUMINOUS FLUX	ORDER CODE
36W 36V 800MA	3000K	4509lm	56.08011
	4000K	4734lm	

**COVIA**

RECESSED DOWNLIGHT



Grille-mounted
Up to 30-degree tilt adjustment
Different power ratings
Customizable length



Quickinfo

2700K, 3000K, 4000K
CRI90, 3 SDCM
L85/50000h
non DIM, 0-10V DIM, DALI-2

Types



Colours



White Black

Light distributions



spot med. flood wide
flood

COVIA

RECESSED DOWNLIGHT

Order options

COLOUR TEMPERATURE

2700K

3000K

4000K

FINISH COLOUR

sandy white

sandy black

BEAM ANGLE COVIA 100 L1

spot 17°

medium 23°

flood 39°

wide flood 52°

BEAM ANGLE COVIA 100 L2

spot 17°

medium 23°

flood 39°

wide flood 52°

BEAM ANGLE COVIA 125 L1

spot 18°

medium 24°

flood 38°

wide flood 47°


BEAM ANGLE COVIA 125 L2

spot 18°


medium 24°

flood 38°

wide flood 47°



100x100




COVIA 100 L1




ADJUSTABLE DOWNLIGHT

SYSTEM POWER	COLOUR TEMP	LUMINOUS FLUX	ORDER CODE
14W 36V 350MA	3000K	1719lm	52.10030
	4000K	1804lm	



190x100




COVIA 100 L2




ADJUSTABLE DOWNLIGHT

SYSTEM POWER	COLOUR TEMP	LUMINOUS FLUX	ORDER CODE
14WX2 36V 350MA	3000K	2X1719lm	52.10031
	4000K	2X1804lm	



125x125



COVIA 125 L1




ADJUSTABLE DOWNLIGHT

SYSTEM POWER	COLOUR TEMP	LUMINOUS FLUX	ORDER CODE
23W 36V 600MA	3000K	2876lm	52.12513
	4000K	3019lm	



245x125



COVIA 125 L2



ADJUSTABLE DOWNLIGHT

SYSTEM POWER	COLOUR TEMP	LUMINOUS FLUX	ORDER CODE
23WX2 36V 600MA	3000K	2X2876lm	52.12515
	4000K	2X3019lm	