



Quickinfo

2700K, 3000K, 4000K
CRI90, 3 SDCM
L85/50000h
non DIM, 0-10V DIM, DALI-2

Types



Colours



White Black

Light distributions



spot med. flood wide
flood

ADJ

SURFACE MOUNTED LIGHT

Order options

COLOUR TEMPERATURE

2700K

3000K

4000K

FINISH COLOUR

matte white

matte black

BEAM ANGLE ADJ 62

spot 20°

medium 25°

flood 38°

wide flood 57°

BEAM ANGLE ADJ 84

spot 24°

medium 30°

flood 44°

wide flood 53°

BEAM ANGLE ADJ 116

spot 19°

medium 25°

flood 41°

wide flood 53°



ADJ 62

CRI >90

COB

350°
25°

IP20



SURFACE MOUNTED LIGHT

SYSTEM POWER	COLOUR TEMP	LUMINOUS FLUX	ORDER CODE
6W 36V 150MA	3000K	445lm	93.06211
	4000K	467lm	



ADJ 84


CRI >90

COB

350°
23°

IP20

DALI



SURFACE MOUNTED LIGHT

SYSTEM POWER	COLOUR TEMP	LUMINOUS FLUX	ORDER CODE
14W 36V 350MA	3000K	1243lm	93.08411
	4000K	1305lm	



ADJ 116


CRI >90

COB

350°
32°

IP20

DALI



SURFACE MOUNTED LIGHT

SYSTEM POWER	COLOUR TEMP	LUMINOUS FLUX	ORDER CODE
20W 36V 500MA	3000K	2190lm	93.11611
	4000K	2299lm	