


Quickinfo

2700K, 3000K, 4000K
CRI90, 3 SDCM
L85/50000h
non DIM, 0-10V DIM, DALI-2

Types**Colours**

White Black

Light distributions

spot med. flood wide
flood

BEAMX

LOW VOLTAGE TRACK LIGHT

Order options

COLOUR TEMPERATURE

2700K

3000K

4000K

FINISH COLOUR

sandy white

sandy black

BEAM ANGLE BEAMX 45

spot 20°

medium 27°

flood 40°

wide flood 55°

BEAM ANGLE BEAMX 53

spot 18°

medium 31°

flood 41°

wide flood 53°

BEAM ANGLE BEAMX 62

spot 17°

medium 27°

flood 37°

wide flood 51°



BEAMX 45

CRI
>90


COB

48V

360°
90°

IP20

DALI



LOW VOLTAGE TRACK LIGHT

SYSTEM POWER	COLOUR TEMP	LUMINOUS FLUX	ORDER CODE
10W 36V 250MA	3000K	903lm	62.04539
	4000K	948lm	



BEAMX 53

CRI
>90


COB

48V

360°
90°

IP20

DALI



LOW VOLTAGE TRACK LIGHT

SYSTEM POWER	COLOUR TEMP	LUMINOUS FLUX	ORDER CODE
15W 36V 350MA	3000K	1396lm	62.05312
	4000K	1465lm	



BEAMX 62

CRI
>90


COB

48V

360°
90°

IP20

DALI



LOW VOLTAGE TRACK LIGHT

SYSTEM POWER	COLOUR TEMP	LUMINOUS FLUX	ORDER CODE
20W 36V 500MA	3000K	1958lm	62.06226
	4000K	2055lm	