


**Quickinfo**

2700K, 3000K, 4000K
CRI90, 3 SDCM
L85/50000h
non DIM, 0-10V DIM, DALI-2

Types**Colours**

White Black

Light distributions

spot med. flood wide
flood

EMMA

LOW VOLTAGE TRACK LIGHT

Order options

COLOUR TEMPERATURE
2700K
3000K
4000K

FINISH COLOUR
sandy white
sandy black

BEAM ANGLE EMMA 45
spot 19°
medium 29°
flood 44°
wide flood 56°

BEAM ANGLE EMMA 62
spot 18°
medium 27°
flood 38°
wide flood 54°

BEAM ANGLE EMMA 73
spot 14°
medium 28°
flood 40°
wide flood 50°



EMMA 45

CRI
>90


COB

48V

360°
90°

IP20

DALI



LOW VOLTAGE TRACK LIGHT

SYSTEM POWER	COLOUR TEMP	LUMINOUS FLUX	ORDER CODE
11W 36V 250MA	3000K	935lm	62.04512
	4000K	981lm	



EMMA 62

CRI
>90


COB

48V

360°
90°

IP20

DALI



LOW VOLTAGE TRACK LIGHT

SYSTEM POWER	COLOUR TEMP	LUMINOUS FLUX	ORDER CODE
14W 36V 350MA	3000K	1627lm	62.06217
	4000K	1708lm	



EMMA 73

CRI
>90


COB

48V

360°
90°

IP20

DALI



LOW VOLTAGE TRACK LIGHT

SYSTEM POWER	COLOUR TEMP	LUMINOUS FLUX	ORDER CODE
24W 36V 600MA	3000K	2963lm	62.07312
	4000K	3111lm	