



Video

MINI

RECESSED DOWNLIGHT






Quickinfo

2700K, 3000K, 4000K
CRI90, 3 SDCM
L85/50000h
non DIM, 0-10V DIM, DALI-2

Types



Colours



White Black

Light distributions



spot med. flood wide
flood

MINI

RECESSED DOWNLIGHT

Order options


COLOUR TEMPERATURE
2700K
3000K
4000K

FINISH COLOUR
matte white
matte black

BEAM ANGLE MINI 30
spot 21°
medium 27°
flood 39°
wide flood 57°

BEAM ANGLE MINI 45
spot 19°
medium 22°
flood 31°
wide flood 46°

BEAM ANGLE MINI 45
spot 19°
medium 22°
flood 31°
wide flood 46°



MINI 30

CRI
>90


COB

IP20

DALI

≤18
UGR

30



RECESSED DOWNLIGHT

SYSTEM POWER	COLOUR TEMP	LUMINOUS FLUX	ORDER CODE
6W 36V 150MA	3000K	353lm	51.03015
	4000K	370lm	



MINI 45

CRI
>90


COB

IP20

DALI

≤18
UGR

45



RECESSED DOWNLIGHT

SYSTEM POWER	COLOUR TEMP	LUMINOUS FLUX	ORDER CODE
6W 36V 150MA	3000K	368lm	51.04511
	4000K	386lm	



MINI 45

CRI
>90

COB


350°
30°

IP20

DALI


≤18
UGR

45



ADJUSTABLE DOWNLIGHT

SYSTEM POWER	COLOUR TEMP	LUMINOUS FLUX	ORDER CODE
6W 36V 150MA	3000K	368lm	52.04512
	4000K	386lm	



Quickinfo

2700K, 3000K, 4000K
CRI90, 3 SDCM
L85/50000h
non DIM, 0-10V DIM, DALI-2

Types



Colours



White Black

Light distributions



spot med. flood wide
flood

MINI

RECESSED DOWNLIGHT

Order options

COLOUR TEMPERATURE
2700K
3000K
4000K

FINISH COLOUR
matte white
matte black

BEAM ANGLE MINI 40
spot 18°
medium 22°
flood 34°
wide flood 46°

BEAM ANGLE MINI 40
spot 18°
medium 22°
flood 34°
wide flood 46°



MINI 40

CRI
>90

COB

IP20

DALI

≤16
UGR



RECESSED DOWNLIGHT

SYSTEM POWER	COLOUR TEMP	LUMINOUS FLUX	ORDER CODE
8W 36V 180MA	3000K	471lm	51.04011
	4000K	494lm	



MINI 40

CRI
>90

COB

IP20

DALI

≤16
UGR



ADJUSTABLE DOWNLIGHT

SYSTEM POWER	COLOUR TEMP	LUMINOUS FLUX	ORDER CODE
8W 36V 180MA	3000K	471lm	52.04018
	4000K	494lm	