


**Quickinfo**

2700K, 3000K, 4000K
CRI90, 3 SDCM
L85/50000h
non DIM, 0-10V DIM, DALI-2

Types**Colours**

White Black

Light distributions

spot med. flood wide
flood

SLIM

RECESSED DOWNLIGHT

Order options

COLOUR TEMPERATURE

2700K

3000K

4000K

FINISH COLOUR

sandy white

sandy black

BEAM ANGLE SLIM 55

spot 25°

medium 32°

flood 42°

wide flood 46°

BEAM ANGLE SLIM 75

spot 30°

medium 40°

flood 46°

wide flood 52°

BEAM ANGLE SLIM 75

spot 31°

medium 40°

flood 46°

wide flood 51°

BEAM ANGLE SLIM 95

spot 27°

medium 32°


flood 41°

wide flood 51°

SLIM 55



55



CRI
>90

COB



IP20


DALI

≤18
UGR


RECESSED DOWNLIGHT

SYSTEM POWER	COLOUR TEMP	LUMINOUS FLUX	ORDER CODE
14W 36V 350MA	3000K	1493lm	51.05516
	4000K	1567lm	

SLIM 75



75



CRI
>90

COB



IP20


DALI

≤17
UGR


RECESSED DOWNLIGHT

SYSTEM POWER	COLOUR TEMP	LUMINOUS FLUX	ORDER CODE
24W 36V 600MA	3000K	2958lm	51.07518
	4000K	3105lm	

SLIM 75



75



CRI
>90

COB



IP20

DALI

≤17
UGR


RECESSED DOWNLIGHT

SYSTEM POWER	COLOUR TEMP	LUMINOUS FLUX	ORDER CODE
32W 36V 800MA	3000K	3530lm	51.07519
	4000K	3706lm	

SLIM 95



95



CRI
>90

COB



IP20

DALI

≤17
UGR

RECESSED DOWNLIGHT

SYSTEM POWER	COLOUR TEMP	LUMINOUS FLUX	ORDER CODE
40W 36V 1050MA	3000K	4374lm	51.09511
	4000K	4592lm	