


**Quickinfo**

2700K, 3000K, 4000K
CRI90, 3 SDCM
L85/50000h
non DIM, 0-10V DIM, DALI-2

Types**Colours**

White Black

Light distributions

spot med. flood wide
flood

SPECTRUM

LOW VOLTAGE TRACK LIGHT

Order options

COLOUR TEMPERATURE

2700K

3000K

4000K

FINISH COLOUR

sandy white

sandy black

BEAM ANGLE SPECTRUM 25

spot 17°

medium 26°

flood 31°

wide flood 53°

BEAM ANGLE SPECTRUM 35

spot 16°

medium 23°

flood 38°

wide flood 49°

BEAM ANGLE SPECTRUM 45

spot 19°

medium 24°

flood 36°

wide flood 43°

BEAM ANGLE SPECTRUM 55

spot 20°

medium 31°

flood 43°

wide flood 52°

SPECTRUM 25



CRI
>90

COB

48V


360°
90°

IP20

DALI

LOW VOLTAGE TRACK LIGHT

SYSTEM POWER	COLOUR TEMP	LUMINOUS FLUX	ORDER CODE
4W 36V 80MA	3000K	197lm	62.02513
	4000K	207lm	



SPECTRUM 35



CRI
>90

COB

48V


360°
90°

IP20

DALI

LOW VOLTAGE TRACK LIGHT

SYSTEM POWER	COLOUR TEMP	LUMINOUS FLUX	ORDER CODE
9W 36V 200MA	3000K	612lm	62.03517
	4000K	643lm	



SPECTRUM 45



CRI
>90

COB

48V


360°
90°

IP20

DALI

LOW VOLTAGE TRACK LIGHT

SYSTEM POWER	COLOUR TEMP	LUMINOUS FLUX	ORDER CODE
15W 36V 350MA	3000K	1083lm	62.04531
	4000K	1137lm	



SPECTRUM 55



CRI
>90

COB

48V

360°
90°

IP20

DALI

LOW VOLTAGE TRACK LIGHT

SYSTEM POWER	COLOUR TEMP	LUMINOUS FLUX	ORDER CODE
25W 36V 600MA	3000K	2615lm	62.05518
	4000K	2743lm	

