

**Quickinfo**

2700K, 3000K, 4000K
CRI90, 3 SDCM
L85/50000h
non DIM, 0-10V DIM, DALI-2

Types**Colours**

White Black

Light distributions

spot med. flood wide
flood

UTH

SURFACE MOUNTED LIGHT

Order options

COLOUR TEMPERATURE
2700K
3000K
4000K

FINISH COLOUR
sandy white
sandy black

BEAM ANGLE UTH 65
spot 21°
medium 27°
flood 35°
wide flood 60°

BEAM ANGLE UTH 80
spot 17°
medium 25°
flood 34°
wide flood 60°

BEAM ANGLE UTH 95
spot 14°
medium 25°
flood 35°
wide flood 58°




UTH 65



SURFACE MOUNTED LIGHT			
SYSTEM POWER	COLOUR TEMP	LUMINOUS FLUX	ORDER CODE
6W 36V 150MA	3000K	562lm	91.06511
	4000K	590lm	




UTH 80



SURFACE MOUNTED LIGHT			
SYSTEM POWER	COLOUR TEMP	LUMINOUS FLUX	ORDER CODE
10W 36V 250MA	3000K	1126lm	91.08011
	4000K	1287lm	



UTH 95



SURFACE MOUNTED LIGHT			
SYSTEM POWER	COLOUR TEMP	LUMINOUS FLUX	ORDER CODE
15W 36V 350MA	3000K	1694lm	91.09511
	4000K	1778lm	